



## Roller 60



### Shaft dimensions

Order Specification		A...M...	A...JGM...
Shaft- $\phi$	EL=		
8	RL+	13	10
10	RL+	12	10

### Tube- and Shaft Combination

Tube dia.	A8	A10	A12	A14
30 x 1	x	x		
30 x 1,8	x			
32 x 2	x	x		
40 x 1,5	x	x	x	x

# Roller 60

<b>Bearing Type</b>	<b>Thermoplastic synthetic material - Bearing Site</b>
Type of Bearing	Ball Bearing (Series 608,6000), 6202 re DIN 625 available in 2RS, ZZ Standard Series 608ZZ
Load Capacity/Roller	600N (depending upon the load limit of tube and shaft)
Max. Speed	1,5 m/s
Range of Temperature Celcius	-5 to +40 C
Optional	
Note	Shaft with Female Thread only in combination with shaft securing (Circlip, Starlock), antistatic version (only for Steel Tube).

## Order Example

Type	60 ZZ - 30x1 STI A8 M8x15 EL=500mm
Bearing Type	60 ZZ
Ball bearing sealing	ZZ
Tube-Ø and wall thickness	30x1
Tube quality	STI
Shaft-Ø	A8
Shaft Ends	M8x15
Installation length	EL=500mm